

MS-9816

Pico-ITX SBC with Intel® Apollo Lake/Apollo Lake-I for Fanless, Low-Power, High-Performance, Wide Temperature & Harsh environment Solution

Industrial Computer

COM Express Board

Pico-ITX Board

3.5" Board


EPIC Board

Mini-ITX Board

Micro-ATX Board

ATX Board

Peripheral



Features

- Intel® Apollo Lake/Apollo Lake-I Series SoC
- LPDDR4 2133 MHz onboard memory up to 4GB
- Triple independent displays: Mini-DP, HDMI, LVDS
- 2 GbE LAN with RJ-45
- 2 USB 3.2 Gen 1, 2 USB 2.0, 2 COM (RS-485), DIO, Audio
- 1 Mini-PCIe (Full size with NANO SIM-Holder), 1 Mini-PCIe (Half size with mSATA) Slots
- SATA 3.0 for storage
- Wide operating temperature : -40~85°C
- DC-IN 12V
- MIPI-CSI 2.0 interface for Camera

Ordering Information

Part Number	Description
919-9816-006	MS-9816 10, Apollo Lake-I E3940 F1 Stepping, Onboard LPDDR4 4GB, 1*HDMI, 1*LVDS, 1*Mini-DP, 1*MIPI, 2*Mini-Pcie, 2*USB3.0, 2*USB2.0, 1*SATA3.0, 2*COM, 2*LAN, DC 12V, SINGLE
919-9816-007	MS-9816 10, Apollo Lake-I E3930 F1 Stepping, Onboard LPDDR4 4GB, 1*HDMI, 1*LVDS, 1*Mini-DP, 1*MIPI, 2*Mini-Pcie, 2*USB3.0, 2*USB2.0, 1*SATA3.0, 2*COM, 2*LAN, DC 12V, SINGLE
919-9816-009	MS-9816 10, Apollo Lake N4200 F1 Stepping, Onboard LPDDR4 4GB, 1*HDMI, 1*LVDS, 1*Mini-DP, 1*MIPI, 2*Mini-Pcie, 2*USB3.0, 2*USB2.0, 1*SATA3.0, 2*COM, 2*LAN, DC 12V, SINGLE
919-9816-010	MS-9816 10, Apollo Lake N3350 F1 Stepping, Onboard LPDDR4 4GB, 1*HDMI, 1*LVDS, 1*Mini-DP, 1*MIPI, 2*Mini-Pcie, 2*USB3.0, 2*USB2.0, 1*SATA3.0, 2*COM, 2*LAN, DC 12V, SINGLE

Packing List

Part Number	Description	Quantity
K14-3018001-V03	COM PORT Cable, 150mm	1
K1B-3008067-V03	USB Cable, 150mm	1
K1D-3010008-V03	SATA Cable with Power, 150mm	1
K1G-3004057-V03	DC Power Cable, 150mm	1

Specifications

Processor	CPU	Apollo Lake SKUs	Apollo Lake-I SKUs
		Intel® Pentium® Processor N4200, QC, 6W Intel® Celeron® Processor N3350, DC, 6W Intel® Celeron® Processor J3455, QC, 10W	Intel® Atom™ x5 Processor E3940, QC, 9.5W Intel® Atom™ x5 Processor E3930, DC, 6.5 W
Memory	Frequency	N4200, 1.1 GHz, up to 2.5 GHz N3350, 1.1 GHz, up to 2.4 GHz J3455, 1.5 GHz, up to 2.3 GHz	E3940, 1.6 GHz, up to 1.8 GHz E3930, 1.3 GHz, up to 1.8 GHz
	L2 Cache	2M	
Display	CPU Type	BGA	
	Chipset	Integrated in SoC	
	BIOS	AMI	
	Technology	Single-channel LPDDR4 2133MHz	
	Max. Capacity	Up to 4GB	
	Socket	Onboard	
	Controller	Intel® HD Graphics	
	Graphic Memory	Depends on CPU	
	LVDS	Dual Channel 18/24-bit	
	eDP	N/A	
Ethernet	Controller	2 x Intel® I211-AT GbE LAN	2 x Intel® I210-IT GbE LAN
	Audio	Controller	Realtek® ALC887-VD2-CG HD Audio Codec
	Super I/O	Controller	Fintek F81866AD-I
	H/W Monitor	Watchdog Timer	256-level Watchdog Timer
I/O Interface	Smart Fan	N/A	
	TPM	Controller	Pin header
	USB	2 x USB 2.0 (internal) 2 x USB 3.2 Gen 1 (rear)	
Expansion Slot	Serial	2 x COM ports (internal) COM1: RS-232/422/485, 0V/5V/12V COM2: RS-232/422/485, 0V/5V/12V	
	GPIO	16-bits (8 x GPI; 8 x GPO), 5V	
Storage	Mini-PCIe	1 x Full-size 1 x Half-size (Mini-PCIe Full-size Slot w/ NANO SIM-Holder) (Mini-PCIe Half-size Slot w/ mSATA)	
	SATA mSATA	1 x SATA 3.0 1 (Shared with Mini-PCIe Half-size)	
Power Supply	DC	DC-in 12V	
	ATX	N/A	
Environment	Operating Temperature	-10 ~ 60°C Note: Thermal w/ Airflow:0.7m/s	-40 ~ 85°C Note: Thermal w/ Airflow:0.7m/s
	Operating Humidity	10 ~ 90%, non-condensing	
	Storage Temperature	-20 ~ 80°C	-40 ~ 85°C
	Storage Humidity	10 ~ 90%, non-condensing	
Form Factor	Dimensions	101 x 73 mm (Pico-ITX)	
	Weight	0.27 kg	
Certification	EMC	FCC, CE, RCM, VCCI, BSMI	
Software Platform	OS Support	Windows 10 IoT Enterprise LTSC/SAC 1809 (64-bit, RS5) Linux (Support by request)	

Optional Item

Part Number	Description
E31-0805900-K08	Heatspreader for Apollo Lake-I
E31-0805910-K08	Heatspreader for Apollo Lake